



THE OPTIPURA COMMITMENT

Optipura™ products are designed with your satisfaction in mind. Our dedication to quality is reflected in our product offerings and service options that are aimed at giving you better returns on your investment. Optipura™ products come with a standard limited factory warranty, including parts and labor. For full service program details in your region, please contact your local representative below.

OVERVIEW

The Optipura minute is a lightweight, portable light duty air treatment device designed for small enclosed spaces with high contaminant or odor levels.

Utilizing high energy light-based technologies, the minute breaks down contaminants using germicidal ultraviolet light, and exciting existing air molecules to highly energized states, also referred to as plasmas*. These plasmas are released into their applied environment and continue to accelerate the breakdown of organic contaminants present.

Because plasmas eventually revert back to their original state and since no chemicals are use, no residues are left behind after they have done their work.

(* Plasmas contain ozone. Regulatory requirements may apply. Supervised use recommended.)

APPLICATIONS

Promotes safer, more comfortable environments:

HAZARDOUS GAS REDUCTION

- Volatile Organic Compounds (alcohols, solvents, formaldehyde, etc.)
- Some Non-Organic gases

HYGIENE IMPROVEMENT

- Lowers airborne and surface microbial count

ODOR REDUCTION

- Reduces excessive or unwanted odors

OTHER ADVANTAGES

- Small form factor
- Lightweight
- Low maintenance

For more information on your specific application, contact your local representative.

TECHNICAL SPECIFICATIONS

Model No	: Minute
Version No	: 3-0
Housing Material	: Powder coated galvanized steel
Dimensions (mm)	: 305 mm (L) x 100 mm (W) x 130 mm (H) / 12.1" (L) x 3.9" (W) x 5.1" (D)
Weight	: 2.1 Kg / 4.6 lbs
Input	: 220-240 V AC, 50/60 Hz (single phase)
Power rating	: 40 W
Fuse rating	: 2A
Ozone output	: 0.15 g/h (approx.)
Air treatment volume	: Up to 1133 cu metres / 40,000 cu feet
Standard Features	: Carry handle Fan filter Detachable Power cable (2.5 m)
Optional accessories	: -
Place for spare fuse	: Yes (spare fuse not provided)
Lamp life	: 5000 hours continuous
Replacement Parts:	: Lamps (model no: 810) x 2 units
Warranty	: Entire Unit - 1 Year : Lamp(s): 6-months; pro-rated

Note: Optipura Asia Pacific Pte Ltd reserves the right to alter product offerings and specifications at any time without notice.

Contact your Optipura dealer today.



Copyright © 2005-2007 Optipura Asia Pacific Pte Ltd.
Optipura™ is a trademark of Optipura Asia Pacific Pte Ltd.
www.optipura.com